			Process Suitability						802		Perspiration ISO 105 E04				2		505			
Meactive [®] & Mohizol [®] Ultra Series			1/1 Standard Depth %	Warm Exhaust	Cold Pad Batch	Pad Dry Pad Steam	Pad Dry Steam	Econtrol	Solubility (g/I) 30°C	CO CO COLOR	Light Source ISO 105 B02			idic		aline	Rubbing Fastness ISO 105 X12		Chlorinated Water ISO 105 EO2	Dischargeability
60°C	0.50%	3.00%	17	War	Colc	Pad	Pad	Eco	Solı	1/6	1/1	Washing ISO3	Е	S	Е	S	Dry	Wet	Chic	Disc
Lemon F4G			3.8	S	NS	NS	NS	NS	150	4-5	5-6	5	4	4	4	4	4	3-4	3-4	D
Yellow CLD			3.5	S	S	S	S	S	100	4-5	5	5	4-5	4-5	4-5	4-5	4-5	4	45	PD
Red CLD			2.5	S	S	S	S	S	150	3-4	4	4-5	4	4	4	4	4-5	4	4	ND
Deep Red CLD			2.0	S	S	S	S	S	100	3-4	4	4-5	4-5	4-5	4-5	4-5	4-5	4	4	ND
Red FD			1.5	S	S	S	NS	NS	100	3-4	4	4	4-5	4	4-5	4	4	4	3	ND
Carmine CLD			1.0	S	S	S	S	S	100	3-4	4	4-5	4-5	4-5	4-5	4-5	4-5	4	3-4	D
Maroon CLD			1.0	S	S	S	S	S	100	3-4	4	4-5	4-5	4	4-5	4	4-5	3	3-4	D
Navy BG			2/1 6	S	S	S	S	S	200	3-4	4	4-5	5	4-5	5	4-5	4	3-4	3	D
Turq Blue G			5.0	S	S	S	S	S	150	5	5-6	3-4	4-5	4-5	5	4-5	4	3	2-3	PD
Sea Blue FR			2.5	S	S	S	S	S	90	5	5-6	4	4-5	4	4-5	4	4-5	3-4	2-3	ND

[•] Ultra Series are higher concentration products which are ideally suitable for medium to higher depth shades. Products are compatible with Meactive DS series, Meactive Bi-functional and Mohizol EPB series.

S = Suitable LS = Less Suitable ND = Not Dischargeable NS = Not Suitable D = Dischargeable PD = Partially Dischargeable