Mohizol® RGB Series

60°C 0.50% 3.00%

			1/1 Standard Depth %	Process Suitability						Light Source ISO 105 B02		Washing ISO3	Perspiration ISO 105 E04				Rubbing Fastness ISO 105 X12		Chlorinated Water ISO 105 EO2	Dischargeability
				Warm Exhaust	Cold Pad Batch	Pad Dry Pad Steam	Pad Dry Steam	Econtrol	Solubility (g/l) 30°C	1/6	1/1		Acidic		Alkaline		Dry	Wet		
													E	S	E	S				
Yellow RGB			1.6	S	S	S	S	S	150	5	5-6	5	4	4	4	4	4-5	4	3	PD
Red RGB			1.6	S	S	S	S	S	100	3	3-4	5	4-5	5	4	5	4	3	3-4	ND
Blue RGB			3.3	S	S	S	S	S	150	3	3-4	4-5	4-5	4-5	4-5	4-5	4	3-4	3	D
Navy Blue RGB			1.6	S	S	S	S	S	150	3	3-4	4-5	4	4	4	4	4	3-4	3-4	D

- Mohizol® RGB Series offer better leveling and robustness properties than commodity dyes and are suitable for a wide variety of shades and dyeing procedures.

S = Suitable
NS = Not Suitable
LS = Less Suitable
D = Dischargeable
ND = Not Dischargeable
PD = Partially Dischargeable